

## SWR

### Residential Duty Swing Gate Operator



Product No. See table below



MODEL	HP	VOLTAGE & PHASE	MAXIMUM GATE WEIGHT	MAXIMUM GATE LENGTH
SWR-211	1/2	115V 1P	500 lbs.	17 ft.
SWR-221		230V 1P		

**Residential duty slide gate operator series, available in 1/2 horsepower, 115V or 230V supply voltage, 11-14 second gate opening speed.**

#### RATINGS

- Maximum duty cycle: 150 cycles per day
- Shipping weight: 140 lbs.

#### FEATURES

- APeX™ Controller
- Black polyethylene cover
- Built-in MegaCode receiver
- Quick disconnect crank assembly
- Exterior reset button
- ETL Listed for UL 325 (Class I-IV) for U.S. and Canada

#### ELECTRICAL

- Integral entrapment sensing system with digital set point for quick accurate adjustment and enhanced safety
- Continuous-tone entrapment alarm with reset button
- LED diagnostic display for ease of setup and troubleshooting
- Selectable pre-start and run alarm with provision for ADA compliant visual pre-start and run alarm
- Regulated 24 Volt DC power available for access control accessories
- Integrated maximum run and auto close timer (0-9 minutes)
- Built-in networked dual gate capability using 3-wire shielded cable

#### MECHANICAL

- Heavy-duty, zinc-plated, steel chassis
- Lockable steel access door
- Universal pad mount standard; optional post mount kit

#### FACTORY OPTIONS

- SPS-50 Standby power supply
- Optional heavy-duty pad mount pedestal
- Optional thermostatically-controlled strip heater
- Cold weather package

#### WARRANTY

- 5 years